

# Gulfcut 86A Non-staining Neat Cutting Oil

# **Product Description**

**Gulfcut 86A** is low viscosity general purpose machining oil and it can be used for machine-tool lubrication as well. This oil is light in colour and additised with anti-mist additives. The resistance to misting exhibited by the oil combined with its superior lubricity makes it an ideal choice for a variety of light duty operations.

#### **Features & Associated Benefits**

Features	Associated Benefits
Low viscosity	Excellent chip flushing ability, good cooling ability
Excellent Anti-misting properties	Cleaner work space, lesser oil loss, acceptability to the operators
Light Colour	Visibility to the operator, close control on machining operations

## **Applications**

- General Purpose Machining
- Automatic Screw Machining
- Honing
- Machine Tool Spindle

**Specifications & Typical Properties** 

Specification			
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Kinematic Viscosity at 40°C, cSt	D 445	5.0	
Flash Point, °C, PMCC	D 93	100	
Density @ 15 °C Kg/l	D 1298	0.8535	
Copper Corrosion	D130	1b	
Active Sulphur		Absent	
Chlorine		Absent	

**Material Compatibility:** 

Ferrous Metals	Yes
Yellow Metals	Yes
Alloys of Aluminium	Yes
Magnesium	Yes

## Handling & Storage guidelines:

- Refer Safety Data Sheets for Health and Safety related information.
- Used product to be disposed by referring to applicable statutory guidelines.
- Store preferably in in-door condition.
- Under normal storage conditions, the product should be consumed within 1 year for optimum performance.

August 2014