

# Gulfcut 36B Non-Staining Neat Cutting Oil

## **Product Description**

**Gulfcut 36B** is neat cutting oil formulated with lubricity additive. This product is ideally suited for heavy duty, high speed and load conditions. The synergy of lubricity additive and chlorinated EP additives imparts protection to work-piece over a broad range of operating conditions. It is light in colour and odour-less in nature.

#### **Features & Associated Benefits**

| Features                         | Associated Benefits                               |  |
|----------------------------------|---|--|
| Presence of lubricity additive   | Improved surface finish, protection of work-piece |  |
| Chlorine based chemistry         | Longer tool life                                  |  |
| Non-reactivity to metal surfaces | No discoloration of work-piece and tool           |  |
| Light Colour                     | Visibility to the operator                        |  |

## **Applications**

- Turning, Milling and Shaping
- Drilling and Boring
- High speed operations

**Specifications & Typical Properties** 

| Specification                    |             | IS 3065-1985 Type 2 Grade II |  |
|----------------------------------|-------------|------------------------------|--|
| Typical Properties               |             |                              |  |
| Test Parameters                  | ASTM Method | Typical Values               |  |
| Kinematic Viscosity at 40°C, cSt | D 445       | 22.0                         |  |
| Flash Point, °C, COC             | D 92        | 171                          |  |
| Density @ 15 °C Kg/l             | D 1298      | 0.8863                       |  |
| Copper Corrosion                 | D130        | 1b                           |  |
| Active Sulphur                   |             | Absent                       |  |
| Chlorine                         |             | Present                      |  |

**Material Compatibility** 

| Ferrous Metals      | Yes                              | Ceramic       | Yes |
|---------------------|----------------------------------|---------------|-----|
| Yellow Metals       | Yes                              | Diamond       | Yes |
| Alloys of Aluminium | Refer to Gulf Oil Representative | Boron Nitride | Yes |

### Handling & Storage guidelines

- Refer Safety Data Sheets for Health and Safety related information.
- Used product to be disposed by referring to applicable statutory guidelines.
- Store preferably in in-door condition.
- Under normal storage conditions, the product should be consumed within 1 year for optimum performance.

August 2014